

ASC-TBH200

銀箭牌

Automatic T-shirt Bottom Hemming Machine 自動T恤下擺折縫機



一次完成針織T-shirt類下擺工段車縫。

此機器搭配左修刀繃縫機，配置電眼偵測放料、自動導布邊和折邊設計、自動導股及自動收料等裝置。

可實現一人多機操作，大幅提升工段的縫製效率和品質，是專業針織T-shirt生產成衣廠必備的高效率生產工具。

Machine operators can handle more than one machine simultaneously.

Greatly improve the sewing efficiency and quality of the workshop, and is an essential high-efficiency production tool for professional knitted T-shirt production garment factories.

特點


FEATURES

- 1 專利導向輪模仿人工手勢，使布料糾偏功能更強大，面料適應性更寬廣。
The patented guide wheel simulates operator's gestures, it makes the machine operating smoothly during the sewing, and applicable for more kinds of fabric.
- 2 專利吹氣倒縫功能，真正實現多股位同方向倒縫。
Patented air-blowing reverse stitching function makes side seams reverse stitching in the same direction.
- 3 起縫和結束線跡完全對齊。
The start and end stitches are perfectly aligned.
- 4 設備自帶衣服大小碼自動調節功能，避免生產中出現混碼而導致縫製錯亂。
The equipment comes with an automatic adjustment function of clothes size, which avoids confusion in sewing caused by mixed sizes in production.
- 5 38-90公分的縫製範圍，可以真正的實現XS到5XL自由切換。
The sewing range of 38-90 cm can sew sizes in between XS to 5XL.
- 6 適用於筒狀或已包邊縫的全自動折下擺車縫。
Fully automatic hemming is suitable for tubular materials or materials with overlock seams.
- 7 可以做第一或最後工序的操作。
It can be the first stage or last stage of production process.
- 8 100%棉質紗線的高速車縫。
High-speed sewing with 100% cotton thread.
- 9 一人可操作多台機器，降低人工縫製難度標準化生產，無需技能工操作。
Machine operators can handle more than one machine simultaneously. Reducing the difficulty of manual sewing and standardizing production, without the need for skilled workers to operate.



規格

SPECIFICATIONS

	Needle No.	mm	mm	mm	S.P.M. (Max)	mm	KG
ASC-TBH200	UY128	 折邊寬度 Hem Width 15~30 mm	標配：5.6， 訂購時可選配 4.0 / 4.8 / 6.4 Normal standard: 5.6 Optional by ordering 4.0 / 4.8 / 6.4	0.3~4.5	4500	L1200 W1200 H1670	180 / 240
生產能力 Capability of Output	80~120 pcs/ hour		適用周長(攤平) Circumference of T-shirt bottom(Flattened)  380-900 mm 對折中心距 Folding center distance				
電源 Power supply	AC 220V，50/60Hz						
工作氣壓 Air Pressure	4 bar						
耗氣量 Air Consumption	190 L / min						
縫紉機機頭 Machine Head			標配：上送筒型 / Normal standard: Top feed cylinder bed type C007KP-W812A-356/CRL/UTP				
標配倒股 Standard seam guide function			要求正、反縫位都可以採用此設備縫製（帶真倒股功能） It can be used to sew both front and back stitching positions (with true back stitch function)				
IOT物聯對接（選配）			IOT interconnection (Please select it when ordering)				
掃線裝置 Sweep the line device			吹氣裝置（標配），電磁鐵勾線裝置（選配） Standard configuration: blowing device Optional Configuration: Electromagnet wire hooking device				



高林股份有限公司
KAULIN MFG. CO., LTD.

由於對產品的改良及更新，本產品型錄中之產品規格及外觀的修改恕不事先通知！
The specification and/or appearances of the equipment described in this catalogue are subject to change without previous notice because of modification.

