

DL8000

Computerized Lockstitch Sewing Machine With
Single Stepping Motor

单步进电脑平缝车



步进马达一拖二结构抬压脚设计、搭载智能主板由核心精准控制针距，精度可达0.1mm的误差。智能控制作动行程、误差，达到精准无声倒缝。

Stepper motor with a one-drag-two structure for presser foot lifting, equipped with an intelligent mainboard for precise stitch length control, achieving an accuracy of 0.1mm. Smart control of motion and error ensures precise and silent reverse stitching

特点

FEATURES

多功能键操作面板：
操作盒按键内容直接，
操作简便迅速




Multi-function key operation panel:
The operation box has direct key content,
and the operation is simple and rapid.

三个按键：
配有三个功能键，方便进行倒缝加固、补针（补1针，补1/2针）操作。



Three buttons:
Equipped with three functional buttons, so that it is convenient for backstitch and stitch compensation (1 stitch, 1/2 stitch).

USB介面：
超能USB介面。



USB interface:
Versatile USB interface equipped.

1 步进马达一拖二结构抬压脚设计
Stepper motor featuring a one-drag-two mechanism,
designed for presser foot lifting

2 出厂预设9种花样缝，也可弹性设定花样，满足多种缝纫需求。
Up to 9 standard sewing patterns for different needs and the
sewing patterns can also be customized upon request.



规格

SPECIFICATIONS

DL8000	mm — — —	mm — — —	mm — — —			Needle No. DB×1	S.P.M. (Max)	自动切线 Auto trimming	倒缝 Reverse Feeding	电子夹线 Thread Gripper	自动 抬压脚 Auto Lifter	可变速量 Adjustable Thread Pick- Up Level
			手动 Hand	膝动 Knee	自动 Auto							
BM1(A)-16Q	0~5 / A : 0~7	15.5	5.5	13	10	#11~#14	4500	V	V	V	V	—
BH1(A)-16Q	0~5 / A : 0~7	18				#20~#23	4500	V	V	V	V	—
BX2(A)-16Q	0~5 / A : 0~7	18				#20~#23	4500	V	V	V	V	—

* A : 表示针板、送具为三排齿 A: Needle plate, feed dog have three gears.
无 : 表示针板、送具为四排齿 None : Needle plate, feed dog have four gears.

高林股份有限公司
KAULIN MFG. CO., LTD.

由於对产品的改良及更新，本产品型录中之产品规格及外观的修改恕不事先通知！
The specification and/or appearances of the equipment described in this catalogue
are subject to change without previous notice because of modification.

FEB. 2025